



A direct link to your customers

– by the number one provider
of mobile communication solutions

LINK Mobility SMS REST API

MO messages

Version 1.1; Last updated June 07, 2017

For help, contact support@linkmobility.com

The most up-to-date version of this document is available at
<http://www.linkmobility.com/developers/>

Contents

Before you begin.....	3
Scope of this document	3
Capabilities of “Common” platform	3
Terms and glossary	3
MO message	3
IP addresses	3
Character encoding.....	3
KeyValue	3
Receiving MO messages.....	4
Examples	6
Example sent to a keyword.....	6
Example sent to a subnumber	8
Changelog of this document.....	9

Before you begin

Please make sure you have provided to Link Mobility Support an URL where Common shall deliver your messages.

Please make an opening in your firewall if necessary so that Common can connect to your system. For a list of the addresses Common will connect from, see below.

Scope of this document

This document will describe the Application Programming Interface (API) to receive text messages through the Link Mobility “Common” platform. Sending messages is described in a separate document.

Common is a REST API. A familiarity with REST APIs is assumed.

Messages will be delivered in JSON format. A basic familiarity with JSON is assumed.

Capabilities of “Common” platform

Common is a high-capacity, high-availability SMS gateway designed to let you send and receive SMS Text messages. Messages can contain any character in the UTF-8 2-byte character set.

Terms and glossary

MO message

Mobile Originated message. Refers to any text message sent from an end-users handset to you.

IP addresses

When delivering a message to you, the requests will be coming from the following IP addresses:

hostname	IP address
socks1.sp247.net	195.84.162.34
socks2.sp247.net	194.71.165.71
socks3.sp247.net	195.84.162.16
socks4.sp247.net	194.71.165.98
socks5.sp247.net	195.84.162.3
socks6.sp247.net	194.71.165.122

Please add openings in your firewalls so that these six hosts can connect to you to deliver messages.

Character encoding

All communication to and from Common will be in UTF-8 encoding.

KeyValue

Contains parameters and values in a JSON object.

Example

```
{ "key1": "value1", "key2": "value2" }
```

Receiving MO messages

When Common forwards an MO message to you, it will be POSTed to your service, in either XML or JSON formats. The format is described in the following table:

Parameter	Data type	Description
destination	String	The shortnumber the message was sent to. Prefixed by a two-letter country code.
subNumber	Integer	If subnumbers are used, the subnumber will be here.
source	String	The phone number of the sender, in MSISDN format (international format)
content	Content	Contains information about the content (text) of the message. See content table below.
operator	String	The telecom operator Common received the message from.
timestamp	DateTime	The timestamp when Common received the message from the operator. Formatted as RFC3339.
messageId	String	Common's internal message ID for this message.
operatorTimestamp	DateTime	The operator-supplied timestamp for the message.
operatorMessageId	String	The operator-supplied message ID for the message.
route	Route	Information on the keyword the message has been matched to, and where the message was routed afterwards. Most fields in this structure are included for debugging purposes, with the exception of "keyword", which contains the keyword matched. The content of route will differ depending on the type of matching used.
gateCustomParameters	KeyValue	If there are custom parameters required for delivery, they will be here. Usually blank.
customParameters	KeyValue	Information from the SMSC which might be mirrored information from other fields, for debugging.

content parameter	Data type	Description
type	String	The type of message. Will usually be "SMS". (MMS is not currently supported by Common)
userData	String	The content of the message sent by the end-user.

content parameter	Data type	Description
encoding	String	The encoding of the message. Will usually be "TEXT".

route parameter	Data type	Description
type	String	Contains information on how the message was routed to you. Contains KEYWORD_ROUTE if the message matched a keyword, or SUBNUMBER_ROUTE if the message matched a subnumber.
id	String	The ID of either the subnumber or the keyword matched.
refId	String	A reference ID for this keyword or subnumber route. This string can be set by Support if you want to use it for routing internally.
gateIds	<List>String	A list of the gate(s) this keyword or subnumber forwards to.
platformId	String	The platformId of the platform which received this message. Will usually be "SMSC".
platformPartnerId	String	Your partnerId
platformServiceType	String	Can be set to any string by Support. Used to differentiate different types of services on your end, if needed.
platformServiceId	String	Can be set to any string by Support. Used to differentiate different services on your end, if needed.
customParameters	KeyValue	Any custom parameters needed for this message. Usually blank.
number	String	The shortnumber this routing rule applies to.
startRange	String	Only if subnumbers are used. Contains the start of the range of subnumbers matched.
stopRange	String	Only if subnumbers are used. Contains the end of subnumbers matched.
keyword	String	Only if keyword is used. Contains the keyword that was matched.
keywordType	String	Contains the type of matching used for this keyword. Support will advise you on the different types of keyword types when setting up the keyword, if needed.
active	Boolean	Whether the keyword is active. Will always be true.

route parameter	Data type	Description
start	DateTime	The start date of the keyword. Will always be in the past.
end	DateTime	The expiry date of the keyword. Will always be in the future.
shared	Boolean	Whether this keyword will forward to multiple services. With the exception of STOP services, this will always be false.
description	String	Human-readable description of the service.

Examples

For most purposes, you are mainly interested in the “source”, “route”:”keyword”, and “content”:”userData” fields. Other fields are included for advanced or debugging purposes.

In these examples, some ID numbers have been replaced with 0.

[Example sent to a keyword](#)

This example is an example of a user with phone number +4741560067 sending a message to shortnumber 2333 with the text “Bclt hello”.

```
{
  "destination": "NO-2333",
  "subNumber": null,
  "source": "+4741560067",
  "content": {
    "type": "SMS",
    "userData": "Bclt hello",
    "encoding": "TEXT"
  },
  "operator": "no.telenor",
  "timestamp": "2015-11-17T14:28:40Z",
  "messageId": "0",
  "operatorTimestamp": "2015-11-17T14:28:40Z",
  "operatorMessageId": "0",
  "route": {
    "type": "KEYWORD_ROUTE",
    "id": "0",
    "refId": "Internal Keyword Reference",
    "gateIds": [
      "0"
    ],
  },
  "platformId": "0",
  "platformPartnerId": "0",
  "platformServiceType": "serviceType",
  "platformServiceId": "Internal Service ID",
  "customParameters": {},
}
```

```
"number": "NO-2333",
"keyword": "BCLT",
"keywordType": "FIRST_WORD",
"active": true,
"start": "2015-11-17T00:00:00Z",
"end": "2016-11-17T00:00:00Z",
"shared": false,
"description": "BCLT service"
},
"gateCustomParameters": {},
"customParameters": {
  "platformPartnerId": "0",
  "suggestedOperator": "no.telenor",
  "moReferenceId": "0",
  "queued": "2015-11-17 15:28:40",
  "serviceCentreTimeStamp": "20151117152840",
  "platformId": "0"
}
}
```

Example sent to a subnumber

This example shows how the request will look when the message is sent to a subnumber rather than a keyword. This example is sent from +4741560067 to shortcode 2333, subnumber 9999999989. The text of the message is "Hello, Dolly!"

```
{
  "destination": "NO-2414",
  "subNumber": 9999999989,
  "source": "+4741560067",
  "content": {
    "type": "SMS",
    "userData": "Hello, Dolly!",
    "encoding": "TEXT"
  },
  "operator": "no.telenor",
  "timestamp": "2015-11-18T11:41:23Z",
  "messageId": "0",
  "operatorTimestamp": "2015-11-18T11:41:23Z",
  "operatorMessageId": "0",
  "route": {
    "type": "SUBNUMBER_ROUTE",
    "id": "0",
    "refId": "SubnumberRange Definition",
    "gateIds": [
      "0"
    ],
    "platformId": "0",
    "platformPartnerId": "0",
    "platformServiceType": "Subnumber messages",
    "platformServiceId": "0",
    "customParameters": {},
    "number": "NO-2333",
    "startRange": "9999999980",
    "stopRange": "9999999989"
  },
  "gateCustomParameters": {},
  "customParameters": {
    "platformPartnerId": "0",
    "suggestedOperator": "no.telenor",
    "moReferenceId": "0",
    "queued": "2015-11-18 12:41:23",
    "serviceCentreTimeStamp": "20151118124123",
    "platformId": "0"
  }
}
```

Changelog of this document

Date	Version	Author	Changes
2015-11-24	1.0	BMS	Initial version
2017-06-07	1.1	KCN	Updated document name and minor changes